



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	60 L/min.
Pilot Ratio	3:1
Maximum Recommended Load Pressure	See Technical Features
Check Cracking Pressure	1,7 bar
Factory Pressure Settings Established at	30 cc/min.
Maximum Valve Leakage at Reseat	0,3 cc/min.
Operating Characteristic	Standard
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.12 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: CBCAXNN

FIXED PRESSURE RANGE	(N)	SEAL MATERIAL	(N)	MATERIAL/COATING
N 2900 - 3500 psi (200 - 245 bar)		N Buna-N		Standard Material/Coating
P 2250 - 2680 psi (155 - 185 bar)		E EPDM		/AP Stainless Steel, Passivated
		V Viton		/LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

