



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-11A
	1
	60 L/min.
	1.5:1
	215 bar
	280 bar
	Sealed
	0,3 cc/min.
	30 cc/min.
-	3.75
	>85% of setting
	22,2 mm
	41 - 47 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.16 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

# OPTION SELECTION EXAMPLE: CBCBLHN

	(L)	(H)	(N)	MATERIAL/COATING
<b>L</b>	<b>H</b>	1000 - 4000 psi 25 psi (70 - 280 bar 1.7 bar), 3000 psi (210 bar)	<b>N</b>	Standard Material/Coating
	<b>A</b>	1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)	<b>V</b>	/AP
	<b>B</b>	400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)		/LH -
	<b>I</b>	400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar)		

## TECHNICAL FEATURES

- 1.3
- 200psi 14bar
- 2 1+ x
- 85%
- Sun
- 4psi 0.3bar
- 3
- "/AP"
- Sun

## PERFORMANCE CURVES

