



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

|  |                           |
|--|---------------------------|
| Pilot Ratio                              | 2:1                       |
| Maximum Recommended Load Pressure        | See Technical Features    |
| Check Cracking Pressure                  | 1,7 bar                   |
| Factory Pressure Settings Established at | 30 cc/min.                |
| Maximum Valve Leakage at Reseat          | 0,3 cc/min.               |
| Seal kit - Cartridge                     | Buna: 990-011-007         |
| Seal kit - Cartridge                     | Polyurethane: 990-011-002 |
| Seal kit - Cartridge                     | Viton: 990-011-006        |
| Seal kit - Cartridge                     | Buna: 990-011-007         |
| Seal kit - Cartridge                     | Polyurethane: 990-011-002 |
| Seal kit - Cartridge                     | Viton: 990-011-006        |

**CONFIGURATION OPTIONS**

Model Code Example: **CBCYXNN**

**FIXED PRESSURE RANGE**

(N)

**SEAL MATERIAL**

(N)

**MATERIAL/COATING**

**N** 2900 - 3500 psi (200 - 245 bar)

**P** 2250 - 2680 psi (155 - 185 bar)

**N** Buna-N

**V** Viton

Standard Material/Coating

**/LH** Mild Steel, Zinc-Nickel