



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-2A
	2
	80 L/min.
	1.5:1
	215 bar
	280 bar
	0,3 cc/min.
	30 cc/min.
-	3.75
	>85% of setting
	28,6 mm
	61 - 68 Nm
	4 mm
	15 mm
	9 - 10 Nm
	0.29 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

# OPTION SELECTION EXAMPLE: CBDBLHN

	(L)	(H)	(N)	MATERIAL/COATING
<b>L</b>	<b>H</b>	<b>H</b>	<b>N</b>	Standard Material/Coating
<b>C</b>	<b>C</b>	<b>A</b>	<b>V</b>	/AP
<b>C</b>	<b>C</b>	<b>B</b>	<b>V</b>	/LH
<b>C</b>	<b>C</b>	<b>I</b>	<b>V</b>	-

## TECHNICAL FEATURES

- 1.3
- 200psi 14bar
- 2 1+ x
- 85%
- Sun
- 4psi 0.3bar
- 3
- Sun

## PERFORMANCE CURVES

