



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-2A |
| | 2 |
| | 80 L/min. |
| | 3:1 |
| | 215 bar |
| | 280 bar |
| | 0,3 cc/min. |
| | 30 cc/min. |
| - | 3.75 |
| | >85% of setting |
| | 28,6 mm |
| | 61 - 68 Nm |
| | 4 mm |
| | 15 mm |
| | 9 - 10 Nm |
| | 0.29 kg. |
| Seal kit - Cartridge | Buna: 990-202-007 |
| Seal kit - Cartridge | Polyurethane: 990-002-002 |
| Seal kit - Cartridge | Viton: 990-202-006 |
| Seal kit - Cartridge | Buna: 990-202-007 |
| Seal kit - Cartridge | Polyurethane: 990-002-002 |
| Seal kit - Cartridge | Viton: 990-202-006 |

OPTION SELECTION EXAMPLE: CBDCLHN

| | (L) | (H) | (N) | MATERIAL/COATING |
|----------|----------|---|---------------|---------------------------|
| L | H | H | N | Standard Material/Coating |
| C | - | 1000 - 4000 psi 25 psi (70 - 280 bar 1.7 bar), 3000 psi (210 bar) | E EPDM | /AP |
| | | A 1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar) | V | /LH |
| | | B 400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar) | | |
| | | I 400 - 1500 psi 25 psi (28 - 105 bar 1.7 bar), 1000 psi (70 bar) | | |

TECHNICAL FEATURES

- 1.3
- 200psi 14bar
- 2 1+ x
- 85%
- Sun
- 4psi 0.3bar
- 3
- Sun

PERFORMANCE CURVES

