



## CONFIGURATION

L Control	Standard Screw Adjustment
H Functional Setting Range	1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting
Material/Coating	

## TECHNICAL DATA

NOTE:

cavidad	T-2A	DATA
Series	2	MAY
Capacity	120 L/min.	VARY
Pilot Ratio	1.5:1	BY
Maximum Recommended Load Pressure at Maximum Setting	215 bar	
Maximum Setting	280 bar	
Adjustment - No. of CCW Turns from Min. to Max. Setting	3.75	
Factory Pressure Settings Established at	30 cc/min.	
Maximum Valve Leakage at Reseat	0,3 cc/min.	
Operating Characteristic	Standard	
Pilot Configuration	Sealed	
Reseat	>85% of setting	
Valve Hex Size	28,6 mm	
Valve Installation Torque	61 - 68 Nm	
Adjustment Screw Internal Hex Size	4 mm	
Locknut Hex Size	15 mm	
Locknut Torque	9 - 10 Nm	
Model Weight	0.29 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	EPDM: 990-202-014	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: CBEBLHN

CONTROL	(L) FUNCTIONAL SETTING RANGE	(H) MATERIAL/COATING	(/LH)
<b>L</b> Standard Screw Adjustment <b>C</b> Tamper Resistant - Factory Set	<b>H</b> 1000 - 4000 psi w/25 psi Check (70 - 280 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting  <b>A</b> 1000 - 4000 psi w/4 psi Check (70 - 280 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting  <b>B</b> 400 - 1500 psi w/4 psi Check (28 - 105 bar w/ 0,3 bar Check), 1000 psi (70 bar) Standard Setting  <b>I</b> 400 - 1500 psi w/25 psi Check (28 - 105 bar w/ 1,7 bar Check), 1000 psi (70 bar) Standard Setting	<b>/LH</b> Mild Steel, Zinc-Nickel  <b>/AP</b> Stainless Steel, Passivated Standard Material/Coating	

## PERFORMANCE CURVES

