



CONFIGURATION

L	400 - 1500 psi 25 psi (28 - 105 bar)
I	1.7 bar (25 psi), 1000 psi (70 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-2A	DATA
	2	MAY
	120 L/min.	VARY
	3:1	BY
	215 bar	
	280 bar	
	Bleed through	
	0,3 cc/min.	
	30 cc/min.	
	3.75	
	>85% of setting	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.29 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

CONFIGURATION. SEE CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: CBEJLIN

	(L)	(I)	(N) MATERIAL/COATING
L	I	N	Standard Material/Coating
	A	V	/LH -
	A		

I 400 - 1500 psi 25 psi (28 - 10 bar 1.7 bar), 1000 psi (70 ba
A 1000 - 4000 psi 4 psi (70 - 280 bar 0.3 bar), 3000 psi (210 bar)

TECHNICAL FEATURES

- 1.3
-
- 200psi 14bar
- 2 1+ x
- 85%
- Sun
- 4psi 0.3bar
- 1000psi 2 3 2in³/min 32cc/min 70bar
- 3
- Sun

PERFORMANCE CURVES

