



**TECHNICAL DATA**

NOTE:

	T-2A	DATA
	2	MAY
	120 L/min.	VARY
	1:1	BY
	215 bar	
	280 bar	
	0,3 cc/min.	
	30 cc/min.	
	3.75	
	>85% of setting	
	28,6 mm	
	61 - 68 Nm	
	4 mm	
	15 mm	
	9 - 10 Nm	
	0.29 kg.	
Seal kit - Cartridge	Buna: 990-202-007	
Seal kit - Cartridge	Polyurethane: 990-002-002	
Seal kit - Cartridge	Viton: 990-202-006	

**CONFIGURATION**

<b>L</b>	
<b>J</b>	2000 - 5000 psi 25 psi (140 - 350 bar 1.7 bar ), 3000 psi (210 bar)
<b>N</b>	
	Material/Coating

CONFIGURATION. SEE CONFIGURATION SECTION.

# OPTION SELECTION EXAMPLE: CBEWLJN

	(L)	(J)	(N)	MATERIAL/COATING
<b>L</b>		<b>J</b>	<b>N</b>	Standard Material/Coating
<b>C</b>	-	<b>2000 - 5000 psi 25 psi (140 - bar 1.7 bar), 3000 psi (210 b</b> <b>B 400 - 1500 psi 4 psi (28 - 105 bar 0.3 bar), 1000 psi (70 bar)</b> <b>C 2000 - 5000 psi 4 psi (140 - 350 bar 0.3 bar), 3000 psi (210 bar)</b> <b>D 1000 - 2500 psi 4 psi (70 - 175 bar 0.3 bar), 2000 psi (140 bar)</b> <b>K 1000 - 2500 psi 25 psi (70 - 175 bar 1.7 bar), 2000 psi (140 bar)</b>	<b>V</b>	/LH -

## TECHNICAL FEATURES

- 1.3
- 
- 200psi 14bar
- 2 1+ x
- 85%
- Sun
- 4psi 0.3bar
- 1000psi 2,3 40in<sup>3</sup>/min 0.7L/min 70bar
- 3
- Sun

## PERFORMANCE CURVES

