



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| Seal kit - Cartridge | Buna: 990-019-007 |
| Seal kit - Cartridge | EPDM: 990-019-014 |
| Seal kit - Cartridge | Polyurethane: 990-019-002 |
| Seal kit - Cartridge | Viton: 990-019-006 |

CONFIGURATION OPTIONS

Model Code Example: CBIHLJN

| CONTROL | (L) | FUNCTIONAL SETTING RANGE | (J) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|---|-----|---|-----|-----------------|-----|--|
| L Standard Screw Adjustment | | J 2000 - 5000 psi w/25 psi Check (140 - 350 bar w/ 1,7 bar Check), 3000 psi (210 bar) Standard Setting | | N Buna-N | | Standard Material/Coating |
| C Tamper Resistant - Factory Set | | C 2000 - 5000 psi w/4 psi Check (140 - 350 bar w/ 0,3 bar Check), 3000 psi (210 bar) Standard Setting | | E EPDM | | /AP Stainless Steel, Passivated |
| | | D 1000 - 2500 psi w/4 psi Check (70 - 175 bar w/ 0,3 bar Check), 2000 psi (140 bar) Standard Setting | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| | | K 1000 - 2500 psi w/25 psi Check (70 - 175 bar w/ 1,7 bar Check), 2000 psi (140 bar) Standard Setting | | | | |