



The back-to-back check valve combines two simple check valves into a single cartridge. It connects the higher of two work ports to the signal or common port. The signal is sensed at an external port located in the hex-end of the cartridge.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Cavity	T-13A
Series	1
Capacity	2.5 gpm
Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	5 drops/min.
Valve Hex Size	7/8 in.
Valve Installation Torque	30 - 35 lbf ft
Model Weight	0.21 lb.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

OPTION SELECTION EXAMPLE: CDAABBN

CONTROL	(B) CRACKING PRESSURE	(B) SEAL MATERIAL	(N) MATERIAL/COATING
B External 1/4 BSPP Port	B 15 psi (1 bar)	N Buna-N	Standard Material/Coating
E External 4-SAE Port		V Viton	IAP Stainless Steel, Passivated

TECHNICAL FEATURES

- Back-to-back check cartridges feature hardened, spherically lapped, guided poppets and a lightly stressed helical spring that result in excellent wear characteristics and extremely low leakage rates.
- The back-to-back checks do not provide a means of lowering a signal. They will trap a high signal if the load pressures drop to a lower pressure. Some means of bleeding off the signal should be provided.
- Incorporates the Sun floating style construction to minimize the possibility of internal parts binding due to excessive installation torque and/or cavity/cartridge machining variations.

PERFORMANCE CURVES

