



## CONFIGURATION

### NOTES:

Modifier

- Stack height value in technical data table includes seal retainer plate.
- This installation requires a retainer and seal kit which are purchased separately. See "Related

Accessories" section.

- **Important:** Carefully consider the maximum system pressure. The pressure rating of the manifold is dependent on the manifold material, with the port type/size a secondary consideration. Manifolds constructed of aluminum are not rated for pressures higher than 3000 psi (210 bar), regardless of the port type/size specified.

### MODIFIER

(Y)

<b>Y</b>	65-45-12 Ductile Iron, Viton, Dewatering Oil
	6061-T651 Aluminum, Buna-N
<b>11</b>	6061-T651 Aluminum, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>10</b>	6061-T651 Aluminum, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>V</b>	6061-T651 Aluminum, Viton
<b>16</b>	6061-T651 Aluminum, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>15</b>	6061-T651 Aluminum, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>M</b>	6061-T651 Aluminum, Metric, Buna-N
<b>1B</b>	6061-T651 Aluminum, Metric, Buna-N, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>1A</b>	6061-T651 Aluminum, Metric, Buna-N, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>Z</b>	6061-T651 Aluminum, Metric, Viton
<b>1G</b>	6061-T651 Aluminum, Metric, Viton, Clear Anodize - Per MIL SPEC 8625F Type II, Class I
<b>1F</b>	6061-T651 Aluminum, Metric, Viton, Black Anodize - Per MIL SPEC 8625F Type II, Class II
<b>S</b>	65-45-12 Ductile Iron, Buna-N, Dewatering Oil
<b>S4</b>	65-45-12 Ductile Iron, Buna-N, Chem. Black
<b>S3</b>	65-45-12 Ductile Iron, Buna-N, Trivalent Clear Zinc with Top Sealer
<b>Y4</b>	65-45-12 Ductile Iron, Viton, Chem. Black
<b>Y3</b>	65-45-12 Ductile Iron, Viton, Trivalent Clear Zinc with Top Sealer
<b>T</b>	65-45-12 Ductile Iron, Metric, Buna-N, Dewatering Oil
<b>T4</b>	65-45-12 Ductile Iron, Metric, Buna-N, Chem. Black
<b>T3</b>	65-45-12 Ductile Iron, Metric, Buna-N, Trivalent Clear Zinc with Top Sealer
<b>W</b>	65-45-12 Ductile Iron, Metric, Viton, Dewatering Oil
<b>W4</b>	65-45-12 Ductile Iron, Metric, Viton, Chem. Black
<b>W3</b>	65-45-12 Ductile Iron, Metric, Viton, Trivalent Clear Zinc with Top Sealer