



CONFIGURATION

X	Control	Not Adustable, Standard Hydraulic Pilot
C	Bias Pressure	30 psi (2 bar)
N	Seal Material	Buna-N
	Material/Coating	

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-163A
Series	0
Capacity	30 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Internal Hex Size	8 mm
Valve Installation Torque	27 - 33 Nm
Model Weight	0.06 kg.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

OPTION SELECTION EXAMPLE: CKBGXCN

CONTROL	BIAS PRESSURE	SEAL MATERIAL	MATERIAL/COATING
(X)	(C)	(N)	(/LH)
X Not Adjustable, Standard Hydraulic Pilot	C 30 psi (2 bar) E 75 psi (5 bar)	N Buna-N V Viton	/LH Mild Steel, Zinc-Nickel /AP Stainless Steel, Passivated Standard Material/Coating

PERFORMANCE CURVES

