



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| cavidad | T-11A |
| Series | 1 |
| Capacity | 60 L/min. |
| Maximum Operating Pressure | 350 bar |
| Pilot Ratio | 3:1 |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,07 cc/min. |
| Valve Hex Size | 22,2 mm |
| Valve Installation Torque | 41 - 47 Nm |
| Model Weight | 0,10 kg |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | EPDM: 990-011-014 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | EPDM: 990-011-014 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

OPTION SELECTION EXAMPLE: CKCBXCFN

| CONTROL | (X) | CRACKING PRESSURE | (C) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|----------|--|-------------------|------------------|---------------|--------|--|
| X | piloto estándar | C | 30 psi (2 bar) | N | Buna-N | Standard Material/Coating |
| B | External 1/4 BSPP Pilot Port, Port 3 blocked | F | 100 psi (7 bar) | E | EPDM | /AP Stainless Steel, Passivated |
| C | Manual Load Release - Tamper Resistant | Z | 1 psi (0,07 bar) | V | Viton | /LH Mild Steel, Zinc-Nickel |
| L | Manual Load Release | | | | | |
| P | External 1/4 NPTF Pilot Port, Port 3 Blocked | | | | | |

PERFORMANCE CURVES

