



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0,10 kg
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	EPDM: 990-011-014
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

## OPTION SELECTION EXAMPLE: CKCDXCFGN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> piloto estándar		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		Standard Material/Coating
<b>B</b> External 1/4 BSPP Pilot Port, Port 3 blocked		<b>F</b> 100 psi (7 bar)		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated
<b>L</b> Manual Load Release		<b>G</b> 150 psi (10,5 bar)		<b>V</b> Viton		<b>/LH</b> Mild Steel, Zinc-Nickel
<b>P</b> External 1/4 NPTF Pilot Port, Port 3 Blocked		<b>Z</b> 1 psi (0,07 bar)				

### PERFORMANCE CURVES

