



CONFIGURATION

V Control	External 1/4 NPTF Pilot Port, Vent to Port 3
C Cracking Pressure	30 psi (2 bar)
N Seal Material	Buna-N

TECHNICAL DATA

NOTE:

cavidad	T-11A	DATA
Series	1	MAY
Capacity	60 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Pilot Ratio	3:1	
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Model Weight	0.11 kg.	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	
Seal kit - Cartridge	Buna: 990-011-007	
Seal kit - Cartridge	Polyurethane: 990-011-002	
Seal kit - Cartridge	Viton: 990-011-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: CKCHVCN

CONTROL

(V) CRACKING PRESSURE

(C) SEAL MATERIAL

(N)

- V External 1/4 NPTF Pilot Port, Vent to Port 3
- S External 4-SAE Pilot Port, Vent to Port 3

- C 30 psi (2 bar)
- F 100 psi (7 bar)

- N Buna-N
- V Viton

PERFORMANCE CURVES

