



**CONFIGURATION**

<b>V</b> Control	External 1/4 NPTF Pilot Port, Vent to Port 3
<b>C</b> Cracking Pressure	30 psi (2 bar)
<b>N</b> Seal Material	Buna-N

**TECHNICAL DATA**

Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

**CONFIGURATION OPTIONS**

**Model Code Example: CKEIVCN**

CONTROL	(V)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)
<b>V</b> External 1/4 NPTF Pilot Port, Vent to Port 3		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N	
<b>S</b> External 4- <small>SAE</small> Pilot Port, Vent to Port 3		<b>F</b> 100 psi (7 bar)		<b>V</b> Viton	