



CONFIGURATION

V Control	External 1/4 NPTF Pilot Port, Vent to Port 3
C Cracking Pressure	30 psi (2 bar)
N Seal Material	Buna-N

NOTE: DATA MAY VARY BASED ON CONFIGURATION. SEE CONFIGURATION SECTION.

TECHNICAL DATA

cavidad	T-2A
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0.28 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

OPTION SELECTION EXAMPLE: CKEIVCN

CONTROL

(V) CRACKING PRESSURE

(C) SEAL MATERIAL

(N)

- V** External 1/4 NPTF Pilot Port, Vent to Port 3
- S** External 4-SAE Pilot Port, Vent to Port 3

- C** 30 psi (2 bar)
- F** 100 psi (7 bar)

- N** Buna-N
- V** Viton

PERFORMANCE CURVES

