



2 1 3 1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	240 L/min.
	350 bar
	3:1
110 SUS (24 cSt)	0,07 cc/min.
	31,8 mm
	203 - 217 Nm
	0,50 kg
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	EPDM: 990-017-014
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

## OPTION SELECTION EXAMPLE: CKGBXCFN

	(X)	(C)	(N)	MATERIAL/COATING
<b>X</b>	<b>C</b> 30 psi (2 bar)	<b>N</b>	Standard Material/Coating	
L	A 4 psi (0,3 bar)	E EPDM	/AP	
	B 15 psi (1 bar)	V	/LH -	
	D 50 psi (3,5 bar)			
	E 75 psi (5 bar)			
	F 100 psi (7 bar)			

### TECHNICAL FEATURES

- 3 3
- 
- 
- 
- 
- 3 E P
- 
- 
- EPDM
- "/AP"
- Sun

### PERFORMANCE CURVES

