



PORT3

PORT2

PORT1

2

1

3

1 2

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-19A
	4
	480 L/min.
	350 bar
	3:1
110 SUS (24 cSt)	0,07 cc/min.
	41,3 mm
	474 - 508 Nm
	1.20 kg.
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006
Seal kit - Cartridge	Buna: 990-019-007
Seal kit - Cartridge	Polyurethane: 990-019-002
Seal kit - Cartridge	Viton: 990-019-006

OPTION SELECTION EXAMPLE: CKIDXCN

	(X)	(C)	(N)	MATERIAL/COATING
X	C 30 psi (2 bar)	N	V	Standard Material/Coating
	A 4 psi (0,3 bar)			/AP
	B 15 psi (1 bar)			/LH -
	D 50 psi (3,5 bar)			
	E 75 psi (5 bar)			
	F 100 psi (7 bar)			

TECHNICAL FEATURES

- 3 3
-
-
-
-
- 3 E P
-
-
-
- "AP"
- Sun

PERFORMANCE CURVES

