



This valve is a fixed-orifice, non-pressure-compensated flow control with a reverse flow check. The flow setting is specified by the user and is set at the factory.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Orifice Range	.016 - .062 in.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

**CONFIGURATION OPTIONS**

**Model Code Example: CNACXCN**

CONTROL	(X)	SETTING RANGE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)		<b>N</b> Buna-N		Standard Material/Coating
		<b>A</b> 4 psi (0,3 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
		<b>E</b> 75 psi (5 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)				<b>/LH</b> Mild Steel, Zinc-Nickel