



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 1,6 mm
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

CONFIGURATION OPTIONS

Model Code Example: CNBCXCN

CONTROL	(X)	SETTING RANGE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Not Adjustable		C 30 psi (2 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)		N Buna-N		Standard Material/Coating
		A 4 psi (0,3 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)		E EPDM		/AP Stainless Steel, Passivated
		B 15 psi (1 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)		V Viton		/LH Mild Steel, Zinc-Nickel
		D 50 psi (3,5 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)				
		E 75 psi (5 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)				
		F 100 psi (7 bar) Cracking Pressure, .016 - .062 in. (0,4 - 1,6 mm)				