


TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-11A
Series	1
Capacity	60 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Orifice Range	0,4 - 3,9 mm
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.13 kg.
Seal kit - Cartridge	Buna: 990-011-007
Seal kit - Cartridge	Polyurethane: 990-011-002
Seal kit - Cartridge	Viton: 990-011-006

OPTION SELECTION EXAMPLE: CNCXCNC

CONTROL	(X) SETTING RANGE	(C) SEAL MATERIAL	(N)
X Not Adjustable	C 30 psi (2 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm) A 4 psi (0,3 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm) B 15 psi (1 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm) D 50 psi (3,5 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm) E 75 psi (5 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm) F 100 psi (7 bar) Cracking Pressure, .016 - .153 in. (0,4 - 3,9 mm)	N Buna-N V Viton	

PERFORMANCE CURVES



Note: Performance data shown reflects a blocked orifice.