



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-5A
	2
	120 L/min.
	350 bar
	0,4 - 3,4 mm
	28,6 mm
	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

OPTION SELECTION EXAMPLE: CNECXCN

	(X)	(C)	(N)	MATERIAL/COATING
X	C	30psi 2 bar .016 - .135 in. (0.4 - 3.4 mm)	N	Standard Material/Coating
		A 4 psi 0.3 bar .016 - .135 in. (0.4 - 3.4 mm)	V	/AP
		B 15psi 1 bar .016 - .135 in. (0.4 - 3.4 mm)		
		D 50 psi 3.5 bar .016 - .135 in. (0.4 - 3.4 mm)		
		E 75 psi 5 bar .016 - .135 in. (0.4 - 3.4 mm)		
		F 100 psi 7bar .016 - .135 in. (0.4 - 3.4 mm)		

TECHNICAL FEATURES

-
- 2
- SUN
- 1 2
-
- Sun

PERFORMANCE CURVES

