



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Orifice Range	0,4 - 3,2 mm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

**CONFIGURATION OPTIONS**

**Model Code Example: CNFCXCN**

CONTROL	(X)	SETTING RANGE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)		<b>N</b> Buna-N		Standard Material/Coating
		<b>A</b> 4 psi (0,3 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
		<b>B</b> 15 psi (1 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)				<b>/LH</b> Mild Steel, Zinc-Nickel
		<b>D</b> 50 psi (3,5 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)				
		<b>E</b> 75 psi (5 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)				
		<b>F</b> 100 psi (7 bar) Cracking Pressure, .016 - .127 in. (0,4 - 3,2 mm)				