



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|----------------------|---------------------------|
| | T-16A |
| | 3 |
| | 240 L/min. |
| | 350 bar |
| | 0,4 - 5,5 mm |
| | 31,8 mm |
| | 203 - 217 Nm |
| | 0.46 kg. |
| Seal kit - Cartridge | Buna: 990-016-007 |
| Seal kit - Cartridge | Polyurethane: 990-016-002 |
| Seal kit - Cartridge | Viton: 990-016-006 |
| Seal kit - Cartridge | Buna: 990-016-007 |
| Seal kit - Cartridge | Polyurethane: 990-016-002 |
| Seal kit - Cartridge | Viton: 990-016-006 |

OPTION SELECTION EXAMPLE: CNGCXCN

| | (X) | (C) | (N) | MATERIAL/COATING |
|---|-----|------------------------------------|-----|---------------------------|
| X | C | 30psi 2 bar .016 - .218 in. (0 mm) | N | Standard Material/Coating |
| | | | V | /AP |

TECHNICAL FEATURES

-
- 2
- SUN
- 1 2
-
- "/AP"
- Sun

PERFORMANCE CURVES

