



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

CONFIGURATION OPTIONS

Model Code Example: **CNGEXCN**

CONTROL	(X)	SETTING RANGE	(C)	SEAL MATERIAL	(N)
X Not Adjustable		C 30 psi (2 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)		N Buna-N	
		A 4 psi (0.3 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)		V Viton	
		B 15 psi (1 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)			
		D 50 psi (3.5 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)			
		E 75 psi (5 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)			
		F 100 psi (7 bar) Cracking Pressure, .016 - .218 in. (0.4 - 5.5 mm)			