



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-17A
Series	3
Capacity	320 L/min.
Orifice Range	0,4 - 6,4 mm
Valve Hex Size	31,8 mm
Valve Installation Torque	203 - 217 Nm
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

## OPTION SELECTION EXAMPLE: CNHEXCN

CONTROL	(X) SETTING RANGE	(C) SEAL MATERIAL (N)
<b>X</b> Not Adjustable	<b>C</b> 30 psi (2 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm) <b>A</b> 4 psi (0,3 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm) <b>B</b> 15 psi (1 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm) <b>D</b> 50 psi (3,5 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm) <b>E</b> 75 psi (5 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm) <b>F</b> 100 psi (7 bar) Cracking Pressure, .016 - .252 in. (0,4 - 6,4 mm)	<b>N</b> Buna-N <b>V</b> Viton