



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-163A
Series	0
Capacity	40 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3.4:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Internal Hex Size	8 mm
Valve Installation Torque	27 - 33 Nm
Model Weight	0,10 kg
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

OPTION SELECTION EXAMPLE: COBGXCFN

CONTROL	(X) CRACKING PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X Not Adjustable, Standard Hydraulic Pilot	C 30 psi (2 bar) F 100 psi (7 bar)	N Buna-N V Viton	Standard Material/Coating /AP Stainless Steel, Passivated

PERFORMANCE CURVES

