



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-2A
Series	2
Capacity	160 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	1.8:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Model Weight	0.23 kg.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	EPDM: 990-202-014
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

OPTION SELECTION EXAMPLE: COFAXCN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X	piloto estándar	C	30 psi (2 bar)	N	Buna-N	Standard Material/Coating
		A	4 psi (0,3 bar)	E	EPDM	/AP Stainless Steel, Passivated
		B	15 psi (1 bar)	V	Viton	/LH Mild Steel, Zinc-Nickel
		D	50 psi (3,5 bar)			
		E	75 psi (5 bar)			
		F	100 psi (7 bar)			
		J	135 psi (9,5 bar)			

PERFORMANCE CURVES

