



This valve is a pilot-to-close check cartridge that has a 120:1 pilot ratio. The valve is designed specifically to discharge an accumulator when the pump is turned off. With no pressure at the pump port (port 3), the valve is open between the accumulator (port 1) and tank (port 2). 60 psi (4 bar) at port 3 will close the valve for accumulator pressures up to 5000 psi (350 bar). When pump pressure at port 3 is below 300 psi (20 bar) there is a leak path from port 3 to tank (port 2) to ensure accumulator discharge when the pump is turned off. When pump pressure is above 300 psi (20 bar) the leak path closes for efficiency.

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	5 drops/min.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

CONFIGURATION OPTIONS

Model Code Example: COFOXDN

CONTROL	(X)	MINIMUM PILOT PRESSURE	(D)	SEAL MATERIAL	(N)
X Standard Pilot		D 60 psi (4 bar)		N Buna-N	
				V Viton	