



1.8 1 1 2 1.8 1 1

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-17A
	3
	320 L/min.
	350 bar
	1.8:1
110 SUS (24 cSt)	0,07 cc/min.
	31,8 mm
	203 - 217 Nm
	0,80 kg
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006
Seal kit - Cartridge	Buna: 990-017-007
Seal kit - Cartridge	Polyurethane: 990-017-002
Seal kit - Cartridge	Viton: 990-017-006

OPTION SELECTION EXAMPLE: COHAXEFGN

	(X)	(E)	(N)	MATERIAL/COATING
X	E 75 psi (5 bar)	N	Standard Material/Coating	
E 4-SAE	A 4 psi (0,3 bar)	E EPDM	/AP	
	B 15 psi (1 bar)	V	/LH -	
	C 30 psi (2 bar)			
	D 50 psi (3,5 bar)			
	F 100 psi (7 bar)			
	G 150 psi (10,5 bar)			
	Z 1 psi (0,07 bar)			

TECHNICAL FEATURES

- 1.8:1 1000psi 70bar 1800psi 125bar 1
- 2
- 2 1
-
- CO*A CO*B CO*A CO*A
- "/AP"
- Sun

PERFORMANCE CURVES

