



## CONFIGURATION

<b>B</b> Control	External 1/4 BSPP Port
<b>X</b> Adjustment Range	-
<b>N</b> Seal Material	Buna-N
Material/Coating	

NOTE: DATA MAY VARY FROM TECHNICAL DATA. SEE CONFIGURATION SECTION.

cavidad	T-13A
Series	1
Capacity	10 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.10 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

## OPTION SELECTION EXAMPLE: CSAABXN

CONTROL	(B) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(N) MATERIAL/COATING (/LH)
<b>B</b> External 1/4 BSPP Port	<b>X</b> -	<b>N</b> Buna-N	<b>/LH</b> Mild Steel, Zinc-Nickel
E External 4-SAE Port		E EPDM	/AP Stainless Steel, Passivated
		V Viton	Standard Material/Coating

### PERFORMANCE CURVES

