



## CONFIGURATION

Adjustment Range

Seal Material

Material/Coating

## TECHNICAL DATA

NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-13A
Series	1
Capacity	10 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Valve Hex Size	22,2 mm
Valve Installation Torque	41 - 47 Nm
Model Weight	0.10 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

## OPTION SELECTION EXAMPLE: CSAAEXN

ADJUSTMENT RANGE

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

(/LH)

X -

N Buna-N

/LH Mild Steel, Zinc-Nickel

E EPDM

/AP Stainless Steel, Passivated

V Viton

Standard Material/Coating

### PERFORMANCE CURVES

