



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

CONFIGURATION OPTIONS

Model Code Example: CSAXXXN

CONTROL	(X) ADJUSTMENT RANGE	(X) SEAL MATERIAL	(N) MATERIAL/COATING
<input checked="" type="checkbox"/> Not Adjustable	<input checked="" type="checkbox"/> -	<input checked="" type="checkbox"/> Buna-N	<input checked="" type="checkbox"/> Standard Material/Coating
<input type="checkbox"/> External 1/4 BSPP Port		<input type="checkbox"/> Viton	<input type="checkbox"/> /AP Stainless Steel, Passivated
<input type="checkbox"/> External 4-SAE Port			<input type="checkbox"/> /LH Mild Steel, Zinc-Nickel