



**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-163A
Series	0
Capacity	4,7 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,3 cc/min.
Valve Hex Size	19,1 mm
Valve Installation Torque	27 - 33 Nm
Model Weight	0.08 kg.
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006
Seal kit - Cartridge	Buna: 990-163-007
Seal kit - Cartridge	Polyurethane: 990-163-002
Seal kit - Cartridge	Viton: 990-163-006

## OPTION SELECTION EXAMPLE: CSAXXXN

CONTROL	(X)	ADJUSTMENT RANGE	(X)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>X</b> -		<b>N</b> Buna-N		Standard Material/Coating
<b>B</b> External 1/4 BSPP Port				<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
<b>E</b> External 4-SAE Port						<b>/LH</b> Mild Steel, Zinc-Nickel

### PERFORMANCE CURVES

