



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| cavidad | T-162A |
| Series | 0 |
| Capacity | 4,7 L/min. |
| Maximum Operating Pressure | 350 bar |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,3 cc/min. |
| Valve Hex Size | 19,1 mm |
| Valve Installation Torque | 27 - 33 Nm |
| Model Weight | 0,10 kg |
| Seal kit - Cartridge | Buna: 990-162-007 |
| Seal kit - Cartridge | Polyurethane: 990-162-002 |
| Seal kit - Cartridge | Viton: 990-162-006 |
| Seal kit - Cartridge | Buna: 990-162-007 |
| Seal kit - Cartridge | Polyurethane: 990-162-002 |
| Seal kit - Cartridge | Viton: 990-162-006 |

OPTION SELECTION EXAMPLE: CSAYXN

ADJUSTMENT RANGE

(X)

SEAL MATERIAL

(N)

MATERIAL/COATING

X -

N Buna-N

Standard Material/Coating

V Viton

/AP Stainless Steel, Passivated

PERFORMANCE CURVES

