



This valve is a pilot to open check valve. It has a sealed pilot, a steel seat, and is vented. It allows free flow from the valve (port 2) to the load (port 1) and blocks flow in the opposite direction. Pressure at the pilot (port 3) will open the valve from port 1 to port 2. Pilot pressure needed to open the valve is directly proportional to the load pressure at port 1. The valve is insensitive to pressure at port 2 because the spring chamber is referenced to the vent (port 4).

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Locknut Hex Size	7/16 in.
Seal kit - Cartridge	Buna: 990-022-007
Seal kit - Cartridge	Polyurethane: 990-022-002
Seal kit - Cartridge	Viton: 990-022-006

CONFIGURATION OPTIONS

Model Code Example: CVEVXCN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
X Standard Pilot		C 30 psi (2 bar)		N Buna-N		Standard Material/Coating
L Manual Load Release		A 4 psi (0,3 bar)		E EPDM		/AP Stainless Steel, Passivated
		B 15 psi (1 bar)		V Viton		/LH Mild Steel, Zinc-Nickel
		D 50 psi (3,5 bar)				
		F 100 psi (7 bar)				