



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-24A
Series	4
Capacity	480 L/min.
Maximum Operating Pressure	350 bar
Pilot Ratio	3:1
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Pilot Passage into Valve	2,3 mm
Pilot Volume Displacement	4,9 cc
Valve Hex Size	41,3 mm
Valve Installation Torque	474 - 508 Nm
Adjustment Screw Internal Hex Size	3,2 mm
Locknut Hex Size	11,1 mm
Model Weight	1,15 kg
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

OPTION SELECTION EXAMPLE: CVIVXCFN

CONTROL	(X) CRACKING PRESSURE	(C) SEAL MATERIAL	(N) MATERIAL/COATING
X piloto estándar	C 30 psi (2 bar)	N Buna-N	Standard Material/Coating
L Manual Load Release	F 100 psi (7 bar)	V Viton	/AP Stainless Steel, Passivated /LH Mild Steel, Zinc-Nickel

PERFORMANCE CURVES

