



2 1 3 1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-24A
	4
	480 L/min.
	350 bar
	3:1
	4,9 cc
110 SUS (24 cSt)	0,07 cc/min.
	2,3 mm
	41,3 mm
	474 - 508 Nm
	3,2 mm
	11,1 mm
	1,15 kg
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006
Seal kit - Cartridge	Buna: 990-024-007
Seal kit - Cartridge	EPDM: 990-024-014
Seal kit - Cartridge	Polyurethane: 990-024-002
Seal kit - Cartridge	Viton: 990-024-006

# OPTION SELECTION EXAMPLE: CVIVXEFN

	(X)	(E)	(N)	MATERIAL/COATING
<b>X</b>	<b>E</b> 75 psi (5 bar)	<b>N</b>	Standard Material/Coating	
<b>L</b>	<b>A</b> 4 psi (0,3 bar)	<b>V</b>	/AP	
	<b>B</b> 15 psi (1 bar)		/LH -	
	<b>C</b> 30 psi (2 bar)			
	<b>D</b> 50 psi (3,5 bar)			
	<b>F</b> 100 psi (7 bar)			

## TECHNICAL FEATURES

- 75psi 5bar
- 4 5000psi 350bar
- 
- 4 4
- 4000 1 0.07cc
- 
- EPDM
- 
- 
- 
- 4
- Sun

## PERFORMANCE CURVES

