



### CONFIGURATION

<b>X</b>	Control	Not Adjustable
<b>C</b>	Cracking Pressure	30 psi (2 bar)
<b>N</b>	Seal Material	Buna-N
	Material/Coating	

Free-flow, nose-to-side check valves are on/off circuit components that allow free flow from the inlet (port 1) to the outlet (port 2) and block flow in the opposite direction.

### TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	EPDM: 990-162-014
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

### CONFIGURATION OPTIONS

#### Model Code Example: CXBAXCN

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
<b>X</b>	Not Adjustable	<b>C</b>	30 psi (2 bar)	<b>N</b>	Buna-N	<b>/LH</b>	Mild Steel, Zinc-Nickel
		<b>A</b>	4 psi (0,3 bar)	<b>E</b>	EPDM	<b>/AP</b>	Stainless Steel, Passivated
		<b>B</b>	15 psi (1 bar)	<b>V</b>	Viton		Standard Material/Coating
		<b>D</b>	50 psi (3,5 bar)				
		<b>E</b>	75 psi (5 bar)				
		<b>F</b>	100 psi (7 bar)				