



CONFIGURATION

| | |
|----------|------------------|
| X | |
| C | 30 psi (2 bar) |
| N | |
| | Material/Coating |

/ 1 2

TECHNICAL DATA

| | |
|----------------------|---------------------------|
| | 350 bar |
| 110 SUS (24 cSt) | 0,07 cc/min. |
| Seal kit - Cartridge | Buna: 990-162-007 |
| Seal kit - Cartridge | EPDM: 990-162-014 |
| Seal kit - Cartridge | Polyurethane: 990-162-002 |
| Seal kit - Cartridge | Viton: 990-162-006 |
| Seal kit - Cartridge | Buna: 990-162-007 |
| Seal kit - Cartridge | EPDM: 990-162-014 |
| Seal kit - Cartridge | Polyurethane: 990-162-002 |
| Seal kit - Cartridge | Viton: 990-162-006 |

CONFIGURATION OPTIONS

Model Code Example: CXBAXCN

| (X) | (C) | (N) | MATERIAL/COATING | (/LH) |
|----------|-------------------------|----------|---------------------------|-------|
| X | C 30 psi (2 bar) | N | /LH - | |
| | A 4 psi (0,3 bar) | E EPDM | /AP | |
| | B 15 psi (1 bar) | V | Standard Material/Coating | |
| | D 50 psi (3,5 bar) | | | |
| | E 75 psi (5 bar) | | | |
| | F 100 psi (7 bar) | | | |
| | Z 1 psi (0,07 bar) | | | |