



/ 1 2

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

	T-162A
	0
	40 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min.
	8 mm
	27 - 33 Nm
	0.03 kg.
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006
Seal kit - Cartridge	Buna: 990-162-007
Seal kit - Cartridge	Polyurethane: 990-162-002
Seal kit - Cartridge	Viton: 990-162-006

## OPTION SELECTION EXAMPLE: CXBGXAN

	(X)	(A)	(N)	MATERIAL/COATING
<b>X</b>	<b>A</b> 4 psi (0,3 bar)	<b>N</b>	<b>Standard Material/Coating</b>	
	<b>B</b> 15 psi (1 bar)	<b>E</b> EPDM	<b>/AP</b>	
	<b>C</b> 30 psi (2 bar)	<b>V</b>	<b>/LH</b>	-
	<b>D</b> 50 psi (3,5 bar)			

### TECHNICAL FEATURES

- - 
  - 
  - 1 2 5000psi 350bar
  - Sun
- 1 0.07cc/min

### PERFORMANCE CURVES

