



TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

| | |
|---|---------------------------|
| Maximum Operating Pressure | 350 bar |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,07 cc/min. |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |
| Seal kit - Cartridge | Buna: 990-011-007 |
| Seal kit - Cartridge | Polyurethane: 990-011-002 |
| Seal kit - Cartridge | Viton: 990-011-006 |

CONFIGURATION OPTIONS

Model Code Example: CXCEXCFN

| CONTROL | (X) | CRACKING PRESSURE | (C) | SEAL MATERIAL | (N) | MATERIAL/COATING |
|-------------------------|-----|-------------------------|-----|-----------------|-----|-----------------------------|
| X Not Adjustable | | C 30 psi (2 bar) | | N Buna-N | | Standard Material/Coating |
| | | A 4 psi (0,3 bar) | | V Viton | | /LH Mild Steel, Zinc-Nickel |
| | | B 15 psi (1 bar) | | | | |
| | | D 50 psi (3,5 bar) | | | | |
| | | E 75 psi (5 bar) | | | | |
| | | F 100 psi (7 bar) | | | | |