



## CONFIGURATION

X	Control	Not Adjustable
A	Cracking Pressure	4 psi (0,3 bar)
N	Seal Material	Buna-N
	Material/Coating	

## TECHNICAL DATA

NOTE:

cavidad	T-13A	DATA
Series	1	MAY
Capacity	80 L/min.	VARY
Maximum Operating Pressure	350 bar	BY
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.	
Valve Hex Size	22,2 mm	
Valve Installation Torque	41 - 47 Nm	
Model Weight	0.11 kg.	
Seal kit - Cartridge	Buna: 990-010-007	
Seal kit - Cartridge	EPDM: 990-010-014	
Seal kit - Cartridge	Polyurethane: 990-010-002	
Seal kit - Cartridge	Viton: 990-010-006	
Seal kit - Cartridge	Buna: 990-010-007	
Seal kit - Cartridge	EPDM: 990-010-014	
Seal kit - Cartridge	Polyurethane: 990-010-002	
Seal kit - Cartridge	Viton: 990-010-006	

CONFIGURATION. SEE  
CONFIGURATION SECTION.

## OPTION SELECTION EXAMPLE: CXDAXAN

CONTROL	(X)	CRACKING PRESSURE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING	(/LH)
<b>X</b> Not Adjustable		<b>A</b> 4 psi (0,3 bar)		<b>N</b> Buna-N		<b>/LH</b> Mild Steel, Zinc-Nickel	
<b>K</b> manilla		<b>F</b> 100 psi (7 bar)		<b>E</b> EPDM		<b>/AP</b> Stainless Steel, Passivated	
<b>L</b> activador manual		<b>G</b> 150 psi (10,5 bar)		<b>V</b> Viton		Standard Material/Coating	
		<b>Z</b> 1 psi (0,07 bar)					

### PERFORMANCE CURVES

