



/ 1 2

CONFIGURATION

X	
A	4 psi (0,3 bar)
N	
	Material/Coating

TECHNICAL DATA

NOTE:

	T-13A	DATA
	1	MAY
	80 L/min.	VARY
	350 bar	BY
110 SUS (24 cSt)	0,07 cc/min.	
	22,2 mm	
	41 - 47 Nm	
	0.11 kg.	
Seal kit - Cartridge	Buna: 990-010-007	
Seal kit - Cartridge	EPDM: 990-010-014	
Seal kit - Cartridge	Polyurethane: 990-010-002	
Seal kit - Cartridge	Viton: 990-010-006	
Seal kit - Cartridge	Buna: 990-010-007	
Seal kit - Cartridge	EPDM: 990-010-014	
Seal kit - Cartridge	Polyurethane: 990-010-002	
Seal kit - Cartridge	Viton: 990-010-006	

CONFIGURATION. SEE
CONFIGURATION SECTION.

OPTION SELECTION EXAMPLE: CXDAXAN

	(X)	(A)	(N)	MATERIAL/COATING	(/LH)
X	A	4 psi (0,3 bar)	N	/LH	-
L	B	15 psi (1 bar)	E	EPDM	/AP
	C	30 psi (2 bar)	V		Standard Material/Coating
	D	50 psi (3,5 bar)			
	E	75 psi (5 bar)			
	F	100 psi (7 bar)			
	G	150 psi (10,5 bar)			
	Z	1 psi (0,07 bar)			

TECHNICAL FEATURES

-
-
- 1 2 5000psi 350bar
- EPDM
- "AP"
- Sun

PERFORMANCE CURVES

