



CONFIGURATION

X	
C	30 psi (2 bar)
N	
Material/Coating	

/ 1 2

NOTE: DATA MAY VARY FROM TECHNICAL DATA SEE CONFIGURATION SECTION.

	T-13A
	1
	80 L/min.
	350 bar
110 SUS (24 cSt)	0,07 cc/min.
	22,2 mm
	41 - 47 Nm
	0.11 kg.
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006
Seal kit - Cartridge	Buna: 990-010-007
Seal kit - Cartridge	EPDM: 990-010-014
Seal kit - Cartridge	Polyurethane: 990-010-002
Seal kit - Cartridge	Viton: 990-010-006

OPTION SELECTION EXAMPLE: CXDAXCN

	(X)	(C)	(N)	MATERIAL/COATING	(/LH)
X	C 30 psi (2 bar)	N	/LH	-	
	A 4 psi (0,3 bar)	E EPDM	/AP		
	B 15 psi (1 bar)	V	Standard Material/Coating		
	D 50 psi (3,5 bar)				
	E 75 psi (5 bar)				
	F 100 psi (7 bar)				

TECHNICAL FEATURES

-
-
- 1 2 5000psi 350bar
- EPDM
- "AP"
- Sun

PERFORMANCE CURVES

