



Free-flow, side-to-nose cheater check valves function as a standard 2-port check valve in a 3-port cavity with port 3 of the cartridge blocked off. These valves are useful in circuits where a check valve is required in an existing three port cavity.

**TECHNICAL DATA** NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

**CONFIGURATION OPTIONS**

**Model Code Example: CXEEXCN**

CONTROL	(X)	CRACKING PRESSURE	(C)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>C</b> 30 psi (2 bar)		<b>N</b> Buna-N		<b>Standard Material/Coating</b>
		<b>A</b> 4 psi (0,3 bar)		<b>V</b> Viton		<b>/AP</b> Stainless Steel, Passivated
		<b>B</b> 15 psi (1 bar)				<b>/LH</b> Mild Steel, Zinc-Nickel
		<b>D</b> 50 psi (3,5 bar)				
		<b>F</b> 100 psi (7 bar)				
		<b>Z</b> 1 psi (0,07 bar)				