



Free-flow, nose-to-side cheater check valves function as a standard 2-port check valve in a 3-port cavity with port 3 of the cartridge blocked off. These valves are useful in circuits where a check valve is required in an existing three port cavity.

### CONFIGURATION

<b>X</b>	Control	Not Adjustable
<b>A</b>	Cracking Pressure	4 psi (0,3 bar)
<b>N</b>	Seal Material	Buna-N
	Material/Coating	

### TECHNICAL DATA

Maximum Operating Pressure	5000 psi
Maximum Valve Leakage at 110 SUS (24 cSt)	1 drops/min.
Seal kit - Cartridge	Buna: 990-202-007
Seal kit - Cartridge	Polyurethane: 990-002-002
Seal kit - Cartridge	Viton: 990-202-006

### CONFIGURATION OPTIONS

#### Model Code Example: CXFCXAN

CONTROL	(X)	CRACKING PRESSURE	(A)	SEAL MATERIAL	(N)	MATERIAL/COATING
<b>X</b> Not Adjustable		<b>A</b> 4 psi (0,3 bar)		<b>N</b> Buna-N		Standard Material/Coating
		<b>B</b> 15 psi (1 bar)		<b>V</b> Viton		<b>LH</b> Mild Steel, Zinc-Nickel
		<b>C</b> 30 psi (2 bar)				
		<b>D</b> 50 psi (3,5 bar)				
		<b>E</b> 75 psi (5 bar)				
		<b>F</b> 100 psi (7 bar)				