



### CONFIGURATION

|   |                   |                 |
|---|-------------------|-----------------|
| X | Control           | Not Adjustable  |
| A | Cracking Pressure | 4 psi (0,3 bar) |
| N | Seal Material     | Buna-N          |
|   | Material/Coating  |                 |

### TECHNICAL DATA

NOTE:

|   |                           |      |
|---|---------------------------|------|
| cavidad                                   | T-2A                      | DATA |
| Series                                    | 2                         | MAY  |
| Capacity                                  | 160 L/min.                | VARY |
| Maximum Operating Pressure                | 350 bar                   | BY   |
| Maximum Valve Leakage at 110 SUS (24 cSt) | 0,07 cc/min.              |      |
| Valve Hex Size                            | 28,6 mm                   |      |
| Valve Installation Torque                 | 61 - 68 Nm                |      |
| Seal kit - Cartridge                      | Buna: 990-202-007         |      |
| Seal kit - Cartridge                      | Polyurethane: 990-002-002 |      |
| Seal kit - Cartridge                      | Viton: 990-202-006        |      |

CONFIGURATION. SEE  
CONFIGURATION SECTION.

## OPTION SELECTION EXAMPLE: CXFCXAN

| CONTROL                 | (X) CRACKING PRESSURE     | (A) SEAL MATERIAL | (N) MATERIAL/COATING               |
|-------------------------|---------------------------|-------------------|------------------------------------|
| <b>X</b> Not Adjustable | <b>A</b> 4 psi (0,3 bar)  | <b>N</b> Buna-N   | Standard Material/Coating          |
|                         | <b>B</b> 15 psi (1 bar)   | <b>V</b> Viton    | <b>/LH</b> Mild Steel, Zinc-Nickel |
|                         | <b>C</b> 30 psi (2 bar)   |                   |                                    |
|                         | <b>D</b> 50 psi (3,5 bar) |                   |                                    |
|                         | <b>E</b> 75 psi (5 bar)   |                   |                                    |
|                         | <b>F</b> 100 psi (7 bar)  |                   |                                    |

### PERFORMANCE CURVES

