



SWITCH SPECIFICATIONS

conector	M12 X 1 (4) Pin
Supply Voltage	20-30 VDC
Operating Temperature Range	-25 to 80 °C
Vibration	≥ 50g, 0-500 impulses/sec
Shock	>50 g, 1ms
Reverse Polarity Protection	Yes
Maximum Output Load	≤ 400 mA, Duty Ratio 100%
Short Circuit Protection	Yes, Load Short Unlimited
Turn On Time	≤ 25 ms
Hysteresis	≤ .002 in.
Thermal Shift - 0 to 80 °C ≤ ±	0,1 mm
EMC	DIN EN 61000-6-1/2/3/4
Connector Environment Rating	IP65
Series	2
Capacity	120 L/min.
Maximum Operating Pressure	350 bar
Maximum Valve Leakage at 110 SUS (24 cSt)	0,07 cc/min.
Transition leakage at 110 SUS (24 cSt)	30 cc/min.@70 bar
Valve Hex Size	28,6 mm
Valve Installation Torque	61 - 68 Nm
Seal kit - Cartridge	Buna: 990-203-007
Seal kit - Cartridge	Viton: 990-203-006

TECHNICAL DATA NOTE: DATA MAY VARY BY CONFIGURATION. SEE CONFIGURATION SECTION.

cavidad	T-5A
---------	------

OPTION SELECTION EXAMPLE: CXFHZCN

CRACKING PRESSURE

(C) SEAL MATERIAL

(N)

C 30 psi (2 bar)

N Buna-N

A 4 psi (0,3 bar)

V Viton